



SPECIFICATIONS

MODEL NUMBER		AOI UH-A7CII	
DESCRIPTION		Underwater Housing for SONY ILCE-7CII Camera	
HOUSING COLOR		AOI UH-A7CII-WHT	AOI UH-A7CII-BLK
		White	Black
COMPATIBLE CAMERA MODEL		SONY ILCE-7CR & ILCE-7CII Camera	
MAIN MATERIAL		PC + GF	
DEPTH RATING		60 Meters	
LENS PORT SYSTEM		AX Port System	
MULTI-CONTROL DEVICE	FLASH CONTROL	a) SONY TTL (Auto HSS), b) Manual Flash	
	WATER LEAKAGE PROTECTION	Built-in Vacuum Analyzation and Wet Detection System (VWS)	
	POWER SOURCE	Built-in Rechargeable Lithium Polymer Battery (3.7V 110mAH)	
	BATTERY CHARGING	By USB Charger DC5V, 0.1A (not included) Approx. 1.5 Hours for a full charge	
	BATTERY OPERATION TIME	Approx. 2 Days (Based on 3 Dives/Day and 1 Hour/Dive)	
DIMENSIONS		197.1mm(L) X 152.7mm(W) X 138.9mm(H)	
WEIGHT		On Land : Approx. 1385.2 g (Only included the Housing Body and Body Cap)	
		Underwater : Approx. -130.0 g (With SONY ILCE-7CII Camera, Camera Batt., FE 28-60mm F4-5.6 Lens, Zoom Gear (AOI LG-SEL-2860), AOI FLP-103 Lens Port and Hot Shoe Connector (AOI HSC-03)	
STANDARD ACCESSORIES		Flat Port for AX Mount Housing for SONY FE 28-60mm F4~5.6 Lens (AOI FLP-103) x1pc.,	
		Zoom Gear for SONY FE 28-60mm F4-5.6 Lens (AOI LG-SEL-2860) x1pc.,	
		Body Cap for AX Mount Housing (AOI BC-101), Hot Shoe Connector (AOI HSC-03) x1pc.,	
		Camera Lens Release Attachment (AOI CLR-02) x1pc.,	
		Spare Main Seal O-ring (AOI SOR-08) x1pc., USB Type-C Charging Cable (AOI USBC-02) x1pc.,	
		Spare Secondary Seal Ring (AOI SSR-06) x1pc., Spare O-ring for Vacuum Valve Protection Cap (AOI SRVV-01) x1pc.,	
		O-ring Remover (AOI ORR-02) x1pc., LCD Hood (AOI LCDH-01) x1pc., Vacuum Hand Pump (AOI VP-03) x1pc.,	
		Extended Shutter Release Lever x1pc., Lanyard (AOI LYD-01) x1pc., Silicone Grease (AOI SIGR-5) x1pc., Silica Gel (AOI SIGE-3) x1pc., Micro-Fiber Cleaning Cloth (AOI MC-01) x1pc.	

*Specifications and Appearances are subject to change without prior notice.