



SPECIFICATIONS

MODEL NUMBER	AOI UH-A7IV	
DESCRIPTION	Underwater Housing for SONY ILCE-7M4 Camera	
HOUSING COLOR	Black	
COMPATIBLE CAMERA MODEL	SONY ILCE-7M4 Camera	
MAIN MATERIAL	PC + GF	
DEPTH RATING	60 Meters	
LENS PORT SYSTEM	AX Port System	
MULTI-CONTROL DEVICE	FLASH CONTROL	a) SONY TTL, b) M-HSS, c) Manual Flash (without Pre-flash)
	WATER LEAKAGE PROTECTION	Built-in Vacuum Analyzation and Wet Detection System (VWS)
	WATER DEPTH MONITOR	Max. Monitoring Depth up to 60 Meters with Preset Depth Alarm Function
	INFORMATION DISPLAY	a) VWS Monitor, b) Water Depth Monitor, c) Depth Alarm, d) Wet Detection Alarm, e) TTL Flash, M-HSS Flash or Manual Flash Selection
	POWER SOURCE	Built-in Rechargeable Lithium Polymer Battery (3.7V 700mAH)
	BATTERY CHARGING	By USB Charger DC5V, 0.5A (not included) Approx. 1.5 Hours for a full charge
	BATTERY OPERATION TIME	18 Hours (continuous operation)
DIMENSIONS	321.5mm(L) X 130.4mm(W) X 203.5mm(H)	
WEIGHT	On Land : Approx. 2890.0 g (Only included the Housing Body and Body Cap)	
	Underwater : Approx. -314.0 g (With SONY ILCE-7M4 Camera, Camera Batt., FE 28-60mm F4-5.6 Lens, AOI FLP-103 Lens Port and Hot Shoe Connector (AOI HSC-03))	
STANDARD ACCESSORIES	Lens Port Front Cap (AOI LFC-101) x1pc., Hot Shoe Connector (AOI HSC-03) x1pc., Camera Tray-01 (AOI CTR-01) x1pc., Spare Main Seal O-ring (AOI SOR-07) x1pc., Spare Secondary Seal Ring (AOI SSR-05) x1pc., Spare O-ring for Vacuum Valve Protection Cap (AOI SRVV-01) x1pc., O-ring Remover (AOI ORR-02) x1pc., LCD Hood (AOI LCDH-01) x1pc., Vacuum Hand Pump (AOI VP-03) x1pc., Silicone Grease (AOI SIGR-5) x1pc., Lanyard (AOI LYD-01) x1pc., Silica Gel (AOI SIGE-3) x1pc., USB Type-C Charging Cable (AOI USBC-02) x1pc., Ball Mount Base (AOI BM-01-BLK) x1pc., Extended Shutter Release Lever x1pc., Allen Key for M6 x1pc., Micro-Fiber Cleaning Cloth (AOI MC-01) x1pc.	

*Specifications and Appearances are subject to change without prior notice.