



SPECIFICATIONS

MODEL NUMBER		AOI UH-A7RV
DESCRIPTION		Underwater Housing for SONY ILCE-7RM5 Camera
HOUSING COLOR		Black
COMPATIBLE CAMERA MODEL		SONY ILCE-7RM5 Camera
MAIN MATERIAL		PC + GF
DEPTH RATING		60 Meters
LENS PORT SYSTEM		AX Port System
MULTI-CONTROL DEVICE	FLASH CONTROL	a) SONY TTL (TTL, HSS TTL), b) Manual Flash (without Pre-flash)
	WATER LEAKAGE PROTECTION	Built-in Vacuum Analyzation and Wet Detection System (VWS)
	WATER DEPTH MONITOR	Max. Monitoring Depth up to 60 Meters with Preset Depth Alarm Function
	INFORMATION DISPLAY	a) VWS Monitor, b) Water Depth Monitor, c) Depth Alarm, d) Wet Detection Alarm, e) TTL Flash or Manual Flash Selection
	POWER SOURCE	Built-in Rechargeable Lithium Polymer Battery (3.7V 700mAH)
	BATTERY CHARGING	By USB Charger DC5V, 0.5A (not included) Approx. 1.5 Hours for a full charge
	BATTERY OPERATION TIME	18 Hours (continuous operation)
	DIMENSIONS	321.5mm(L) X 130.4mm(W) X 203.5mm(H)
WEIGHT		On Land : Approx. 2005.0 g (Only included the Housing Body and Body Cap)
		Underwater : Approx. -1326 g (With SONY ILCE-7RM5 Camera, Camera Batt., FE 28-60mm F4-5.6 Lens, AOI FLP-103 Lens Port and Hot Shoe Connector (AOI HSC-03))
STANDARD ACCESSORIES		Body Cap (AOI BC-101) x1pc., Hot Shoe Connector (AOI HSC-03) x1pc.,
		Camera Tray-01 (AOI CTR-01) x1pc., Spare Main Seal O-ring (AOI SOR-07) x1pc.,
		Spare Secondary Seal Ring (AOI SSR-05) x1pc., Spare O-ring for Vacuum Valve Protection Cap (AOI SRVV-01) x1pc.
		O-ring Remover (AOI ORR-02) x1pc., LCD Hood (AOI LCDH-01) x1pc., Vacuum Hand Pump (AOI VP-03) x1pc.,
		Silicone Grease (AOI SIGR-5) x1pc., Lanyard (AOI LYD-01) x1pc., Silica Gel (AOI SIGE-3) x1pc.,
		Ball Mount Base (AOI BM-01-BLK) x1pc., Alen Key for M6 x1pc., Micro-Fiber Cleaning Cloth (AOI MC-01) x1pc.

*Specifications and Appearances are subject to change without prior notice.