



SPECIFICATIONS

MODEL NUMBER	AOI UH-EM10 IV	
DESCRIPTION	Underwater Housing for Olympus OM-D E-M10 Mark IV	
HOUSING COLOR	AOI UH-EM10 IV-WHT	AOI UH-EM10 IV-BLK
	White	Black
COMPATIBLE CAMERA MODELS	Olympus OM-D E-M10 Mark IV	
MAIN MATERIAL	Housing Body: Polycarbonate	
DEPTH RATING	45 Meters	
LENS PORT SYSTEM	AOI / Olympus PEN Ports System	
BUILT-IN LED FLASH TRIGGER	Compatible with a) Manual Flash Trigger (with and without Pre-flashes Functions) b) Olympus RC Mode (TTL AUTO, MANUAL, FP TTL AUTO, FP MANUAL)	
WATER LEAKAGE PROTECTION	Built-in Vacuum Analyzation and Wet Detection System (VWS)	
BATTERY POWER	Built-in Rechargeable Lithium Polymer Battery (3.7V 110mAh)	
BATTERY CHARGING	By USB Charger DC5V, 0.5A (not included) Approx. 1.5 Hours for a full charge	
BATTERY OPERATION TIME	Approx. 2 Days (Based on 3 Dives/Day and 1 Hour/Dive)	
DIMENSIONS	177.9mm (W) x 139.8mm (H) x 151.2mm (D)	
WEIGHT	On Land : Approx.835 g	
	(Only included the Housing Body and Flat Port)	
STANDARD ACCESSORIES	Flat Port (AOI FLP-06); Lens Gear (AOI LG-OM-1442EZ)	
	Hot Shoe Connector (AOI HSC-02); USB Type-C Charging Cable (AOI USBC-02)	
	Vacuum Pump (AOI VP-02); LCD Monitor Hood (LCDH-01)	
	Spare O-Ring for Vacuum Valve Protection Cap x 1pc. (AOI SRVV-01)	
	Spare Main Seal O-ring x 1pc. (AOI HOR-01)	
	Silica Gel (AOI SIGE-3) x 1pc.; Silicone Grease (AOI SIGR-5)	
	Lanyard (AOI LYD-01); Port Front Cap for M67 Thread (AOI LFC-01)	
	Port Rear Cap for PEN Mount (AOI PRC-02); O-ring Remover (AOI ORR-02)	
Micro-Fiber Cleaning Cloth (AOI MC-01); AOI Logo Sticker		

*Specifications and Appearances are subject to change without prior notice.