



SPECIFICATIONS

MODEL NUMBER	AOI UH-EPL10R-WHT
DESCRIPTION	Underwater Housing for Olympus E-PL9/10 with RC Mode - White Color
COMPATIBLE CAMERA MODELS	Olympus PEN E-PL9 or E-PL10 with kit lens M.ZUIKO DIGITAL ED 14-42mm F3.5-5.6 EZ
MAIN MATERIAL	Housing Body : Polycarbonate
	Flat Port Glass : Optical Glass with double sided multi-layer AR coating
DEPTH RATING	45 Meters
BUILT-IN LED FLASH TRIGGER	Compatible with a) Manual Flash Trigger (with and without Pre-flashes Function) b) Olympus RC Mode (TTL AUTO, MANUAL, FP TTL AUTO, FP MANUAL)
WATER LEAKAGE PROTECTION	Built-in Vacuum Analyzation and Wet Detection System (VWS)
BATTERY POWER	Built-in Rechargeable Lithium Polymer Battery (3.7V 110mAH)
BATTERY CHARGING	By USB Charger DC5V, 0.5A (not included) Approx. 1.5 Hours for a full charge
BATTERY OPERATION TIME	Approx. 2 days (Based on 3 Dives/Day and 1 Hour/Dive)
DIMENSIONS	Approx. 166mm (W) x 128mm (H) x 135.5mm (D)
WEIGHT	On Land : Approx. 734g (Only included the Housing Body and Kit Port)
	Underwater : Approx. 26g (Only included the Housing Body and Kit Port)
STANDARD ACCESSORIES	Flat Port (AOI FLP-06-GRY); USB Type-C Charging Cable Lens Gear (AOI LG-OM-1442EZ); Vacuum Pump (AOI VP-02) Hot Shoe Connector (AOI HSC-02); Extended Shutter Release Lever Spare Main Seal-ring x 1pc. (AOI HOR-01); O-ring Remover (AOI ORR-02) Spare O-ring for Vacuum Valve Protection Cap x 1pc. (AOI SRVV-01) Silica Gel (AOI SIGE-3) X 3pcs.; Silicone Grease (AOI SIGR-5) Port Front Cap for M67 Thread (AOI LFC-01); Port Rear Cap for PEN Mount (AOI PRC-02) Lanyard (AOI LYD-01); LCD Monitor Hood

*Specifications and Appearances are subject to change without prior notice.