



SPECIFICATIONS

MODEL NUMBER	AOI UH-OM1
DESCRIPTION	Underwater Housing for OM SYSTEM OM-1
HOUSING COLOR	Black
COMPATIBLE CAMERA MODELS	Olympus OM System OM-1
MAIN MATERIAL	Housing Body: Polycarbonate
DEPTH RATING	45 Meters
LENS PORT SYSTEM	AOI / Olympus PEN Ports System
BUILT-IN LED FLASH TRIGGER	Compatible with a) Manual Flash Trigger (with and without Pre-flashes Functions) b) Olympus RC Mode (TTL AUTO, MANUAL, FP TTL AUTO, FP MANUAL)
WATER LEAKAGE PROTECTION	Built-in Vacuum Analyzation and Wet Detection System (VWS)
BATTERY POWER	Built-in Rechargeable Lithium Polymer Battery (3.7V 220mAH)
BATTERY CHARGING	By USB Charger DC5V, 0.5A (not included) Approx. 1.5 Hours for a full charge
BATTERY OPERATION TIME	Approx. 4 Days (Based on 3 Dives/Day and 1 Hour/Dive)
DIMENSIONS	195.9mm (W) x 129.7mm (H) x 149.7mm (D)
WEIGHT	On Land : Approx.1079 grams (Only included the Housing Body and Body Cap)
STANDARD ACCESSORIES	Body Cap / Storage Box for PEN Mount Housing (AOI BC-02)
	USB Type-C Charging Cable; LCD Monitor Hood
	Spare O-Ring for Vacuum Valve Protection Cap x1pc. (AOI SRVV-01)
	Vacuum Pump (AOI VP-02); Spare Main Seal O-Ring x1pc. (AOI SOR-04)
	Spare Secondary Seal Ring x1pc. (AOI SSR-03); Silicone Grease (AOI SGR-5)
	Silica Gel (AOI SIGE-3) x 1pc.; Lanyard (AOI LYD-01)
O-ring Remover (AOI ORR-02) ; Hot Shoe Connector (AOI HSC-02)	

*Specifications and Appearances are subject to change without prior notice.