



SPECIFICATIONS

MODEL NUMBER	AOI UH-OM5 II	
DESCRIPTION	Underwater Housing for OM System OM-5 Mark II Camera	
HOUSING COLOR	Translucent Grey	
COMPATIBLE CAMERA MODELS	OM SYSTEM OM-5 Mark II	
	OM SYSTEM OM-5 and EM-5 III (must be Converted by CNK-002)	
MAIN MATERIAL	Housing Body: Polycarbonate	
DEPTH RATING	60 Meters	
LENS PORT SYSTEM	AOI / OLYMPUS OM-D Ports System	
STROBE TRIGGER (WITH M & RC-TTL FUNCTIONS)	AOI STR-05 (Standard Accessory), or OLYMPUS FL-LM3 (Optional Accessory)	
WATER LEAKAGE PROTECTION	Built-in Vacuum Analyzation and Wet Detection System (VWS)	
	BATTERY POWER	Built-in Rechargeable Lithium Polymer Battery (3.7V)
	BATTERY CHARGING	By USB Charger DC5V, 0.5A (not included) Approx. 1.5 Hours for a full charge
	BATTERY OPERATION TIME	Approx. 100 hours
DIMENSIONS	206.20mm (W) x 181.70mm (H) x 113.55mm (D)	
WEIGHT	On Land : Approx. 1340g (Only included LCD Monitor Hood and Lanyard)	
STANDARD ACCESSORIES	Conversion Kit (AOI CNK-002); LED Strobe Trigger (AOI STR-05)	
	Body Cap / Storage Box for OM-D Mount Housing (AOI BC-01)	
	USB Type-C Charging Cable (AOI USBC-02)	
	LCD Monitor Hood (AOI LCDH-01)	
	Spare O-Ring for Vacuum Valve Protection Cap x 1pc. (AOI SRVV-01)	
	Vacuum Pump (AOI VP-02); Extended Shutter Release Lever (AOI ESL-02-GRY)	
	O-Ring Remover (AOI ORR-02); Spare Main Seal O-Ring x 1pc. (AOI SOR-02)	
	Spare Secondary Seal Ring x 1pc. (AOI SSR-02)	
	Silicone Grease (AOI SIGR-5); Silica Gel (AOI SIGE-3) x 1pc.	
	Lanyard (AOI LYD-01); Fiber Optic Cable Port Plug x 2pcs. (AOI OCP-PS-05)	

*Specifications and Appearances are subject to change without prior notice.