



SPECIFICATIONS

MODEL NUMBER	AOI UH-OM5
DESCRIPTION	Underwater Housing for OM System OM-5 Camera
HOUSING COLOR	AOI UH-OM5-TGRY Translucent Grey
COMPATIBLE CAMERA MODELS	OM System OM-5
MAIN MATERIAL	Housing Body: Polycarbonate
DEPTH RATING	60 Meters
LENS PORT SYSTEM	AOI / Olympus OM-D Ports System
WATER LEAKAGE PROTECTION	Built-in Vacuum Analyzation and Wet Detection System (VWS)
BATTERY POWER	Built-in Rechargeable Lithium Polymer Battery (3.7V)
BATTERY CHARGING	By USB Charger DC5V, 0.5A (not included) Approx. 1.5 Hours for a full charge
BATTERY OPERATION TIME	Approx. 100 hours
DIMENSIONS	206.20mm (W) x 181.70mm (H) x 113.55mm (D)
WEIGHT	On Land : Approx. 1340g (Only included LCD Monitor Hood and Lanyard)
STANDARD ACCESSORIES	Body Cap / Storage Box for OM-D Mount Housing (AOI BC-01)
	USB Type-C Charging Cable (AOI USBC-02)
	LCD Monitor Hood (AOI LCDH-01)
	Spare O-Ring for Vacuum Valve Protection Cap x 1pc. (AOI SRVV-01)
	Vacuum Pump (AOI VP-02); Extended Shutter Release Lever (AOI ESL-02-TGRY)
	Spare Main Seal O-Ring x 1pc. (AOI SOR-02)
	Spare Secondary Seal Ring x 1pc. (AOI SSR-02)
	Silicone Grease (AOI SIGR-5); Silica Gel (AOI SIGE-3) x 1pc.
	Lanyard (AOI LYD-01); Fiber Optic Cable Port Plug x 2pcs. (AOI OCP-PS-05)
	O-Ring Remover (AOI ORR-02); Led Strobe Trigger (AOI STR-05)

*Specifications and Appearances are subject to change without prior notice.