



## SPECIFICATIONS

MODEL	AOI UWL-09 PRO
DESCRIPTION	Underwater 0.45X Wide Angle Conversion Lens
LENS CONSTRUCTION	6 Elements in 6 Groups
LENS COATING	All Glass Lens Elements with Multi-layers AR Coating, Optical Grade Glass Dome Lens with Inner Surface Multi-layers AR Coating
FIELD OF VIEW (DIAGONAL)	130° (with 28mm Lens)
MAGNIFICATION	0.45X
MINIMUM OBJECT DISTANT	0 mm to the Front Dome Lens
MOUNT SYSTEM	M67 Thread
DEPTH RATING	100 Meters / 330 Ft.
LENS BARREL / LENS HOOD	Aluminum Alloy with Black Hard Anodized
WEIGHT (ON LAND / UNDERWATER)	1408 g (on land) 770 g (underwater)
DIMENSIONS	139.2mm (D) X98.9mm (H)
STANDARD ACCESSORIES	Neoprene Dome Front Cover (DNC-04), Rear Lens Cap (LRC-02), Lens Secure Line (LSL-02), Type B M67 Adapter (UWL-09P-Type B) with Allen Key and Carry Case (LPC-02)

\*Specifications and Appearances are subject to change without prior notice.