



SPECIFICATIONS

MODEL	AOI UWL-400A
DESCRIPTION	Underwater 0.50X Wide Angle Conversion Lens (Not Included QRS-01-AD3)
LENS CONSTRUCTION	5 Elements in 5 Groups
LENS COATING	All Glass Lens Elements with Multi-layers AR Coating, Front PC Dome Lens with Hard Coating
FIELD OF VIEW (DIAGONAL)	Underwater 120° (with 25mm Lens)
MAGNIFICATION	0.50X (on land / underwater)
MINIMUM OBJECT DISTANT	0 mm to the Front Dome Lens (on land / underwater)
MOUNT SYSTEM	M52 Thread changeable for quick release adapter
DEPTH RATING	100 Meters / 330 Ft.
LENS BARREL / LENS HOOD	Aluminum Alloy with Black HardAnodized / ABS
WEIGHT (ON LAND / UNDERWATER)	618g (on land) 224g (underwater)
DIMENSIONS	121.8mm (D) X 76mm (H)
STANDARD ACCESSORIES	Neoprene Dome Cover (DNC-02), Rear Lens Cap (LRC-01), Lens Secure Line (LSL-03) and Carry Case(LPC-04)

*Specifications and Appearances are subject to change without prior notice.