



SPECIFICATIONS

MODEL	AOI VWS-02-M16	
DESCRIPTION	Vacuum Analyzation & Wet Detection System Kit	
VALVE FASTENING	M16	
VALVE MATERIAL	Black Anodized Aluminum Alloy	
DEPTH RATED	100M / 330Ft	
CHARGING TIME	1.5 Hours	
CHARGING PORT	5V, 0.3A Micro-USB charging Port	
POWER SWITCH	Sliding ON / OFF Switch	
OPERATION TIME PER FULL CHARGE	4 Days (Powered by 3.7V 110mAH Lithium Polymer Rechargeable Battery)	
VACUUM ANALYZING TIME	Approx. 4 Minutes	
WET DETECTION	All time Operation	
INDICATOR SIGNAL OUTPUT	Piezo Buzzer (Audio Signal)	
	Tri-color LED (Blue, Yellow, Red & Green Visual Signals)	
DIMENSIONS	Vacuum Valve	Φ 22 x 34 mm (H)
	Main Unit	28 mm (L) x 18mm (W) x 7 mm (H)
	Signaling & Charging Unit	30 mm (L) x 14mm (W) x 7 mm (H)
	Long Connection Cable	140 mm (L) x 5 mm (W)
	Short Connection Cable	75 mm (L) x 5 mm (W)
	Extension Visual Signal Board Cable	120 mm (L) x 3 mm (W)
WEIGHT	Vacuum Valve	16.5 g
	Main Unit	5.5 g
	Signaling & Charging Unit	2.8 g
ACCESSORIES	Vacuum Pump Multi Purpose Key	

*Specifications and Appearances are subject to change without prior notice.